



FillCleaner EVO

ECOLOGICAL DETERGENT FOR THE REMOVAL OF RESIDUE LEFT BY GROUTING PERFORMED WITH FILLGOOD EVO, THE SINGLE COMPONENT, READY-TO-USE, WATER-BASED POLYURETHANE GROUT.



DESCRIPTION

FillCleaner EVO is an ecological detergent with neutral pH, delicate on ceramic surfaces, comprised of ingredients derived from natural, completely biodegradable substances.

FIELDS OF APPLICATION

FillCleaner EVO is the specific cleaner used to remove resinous residue left by grouting performed using the polymeric mortar for joints, FillGood EVO, from the surface of tiles and vitreous mosaics. Its high viscosity makes it also perfect for wall applications with no dripping. The product is very efficient on surface residue without damaging the polymeric mortar used in the joints. FillCleaner EVO is also perfect as a degreaser for ceramic surfaces in contact with foodstuffs, such as kitchen countertops.

APPLICATION

Any clear halos on the surface of ceramic, porcelain or mosaic tiles, due to the film formed by the resin in the FillGood EVO polymeric mortar, must be removed after at least 24 hours from grouting using the neutral cleaner FillCleaner EVO.

Spread the pure product onto the surface and after a few minutes, rub with some white felt (art. 109GBNC), then rinse with a damp sponge and dry the surface with a clean cloth. It is recommended to apply FillCleaner EVO on limited surface areas (about 1- 2 m²) so that it does not remain in contact with the grouting for more than 5 - 7 minutes.

WARNINGS

- Use the product pure, undiluted
- FillCleaner EVO must be used to clean after at least 24 hours from grouting with FillGood EVO.
- Do not use the product for applications not specifically stated in this data sheet.

PACKAGING

Bottles with spray nozzle 0.75 litres. Boxes of 12 pcs.

SAFETY INFORMATION

Consult the product safety data sheet, available on request.

PRODUCT FOR PROFESSIONAL USE



IDENTIFICATION DATA

Appearance	Colourless clear gel
Odour	Characteristic
Specific gravity of mix	995 ± 10 g/l
pH (5% in water)	6.5 - 7.5
Customs code	3402 90 90
Shelf life	24 months in original packaging in a cool, dry environment. Keep away from frost.
Consumption	10 m ² / per bottle

APPLICATION DATA

Equipment	White felt (art. 109GBNC) sponge
Application temperatures allowed	From +5°C to +30°C
Ready for cleaning	After at least 24 hours from grouting with FillGood EVO
Maximum contact time on grouting	No more than 5-7minutes

Although the information provided in this technical data sheet is accurate to the best of our knowledge and experience, it is intended purely as a guideline.
The user must carry out preliminary practical tests before each use and is solely responsible for the final result.

Sheet no. 321

Revision no. 2

Date: November 2019

LITOKOL S.p.A.

Via G. Falcone, 13/1 42048 Rubiera (RE) Italy

Tel. +39 0522 622811 Fax +39 0522 620150

Www.litokol.it email: info@litokol.it

**COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =**